

MIG 200 MULTI

DUTY CYCLE 60%



PROFESSIONAL LINE



Includes:



pure cooper 3m



pure cooper 3m



Easy inversion of Polarity



Advantages

- Electronic welding equipment suitable for (MIG / MAG, flux core), TIG and all type of covered electrodes.
- Solid manufacturing under European regulations 2011/65 / EU, 2014/35 / EU, 2014/30 / EU and IEC 60974.
- New reel container with professional large capacity (15kg).
- Wire feeder traction mechanism with universal roller of 0.6 mm (steel) & 0.9 mm (flux core).
- Easy regulation: classic analogic controls for precise adjustment of current, voltage and wire speed.
- Simple and fast inversion of polarity to weld hollow wire without protection gas.
- The working mode MMA (rod) includes the advantages of Hot Start, Arc Force and Anti Stick to optimize the initial priming of the arc, improve its stability during welding and prevent electrode from sticking due to mishandling.
- Ready for TIG Welding (Torch not included)
- Ready for all kind of stabilized generators: condenser, AVT and Inverter systems.
- Available: input current limiter for safe use in house, hospital, etc

Includes:

- Main input cable 3m x 2,5mm²
- Ground clamp and cable 3m x 25mm²
- Electrode clamp and holder 3m x 25mm²
- External wire feeder 15kg
- BINZEL Torch 15AK / 3m.
- Wheels.

Features

Power (Amps) (A, X=60%)	200
Wire (mm)	0.8 - 1.0
Electrode (mm)	5
Weight (Kg)	22
Voltage (V)	230
Generator (KVA)	6
Dimensions (cm)	23 x 50 x 36

All accessories available in our catalogue.

STAYER MIG 200 MULTI - komplet

Multisistemski uređaj snage 200 A za **MIG-MAG/REL/TIG** zavarivanje

MIG-MAG zavarivanje žicama do ϕ 1,0mm

REL zavarivanje obloženim elektrodama (sa ugradjenim funkcijama **Hotstart**, **AntiStick** i **Arc-Force**)

TIG-DC (ContactTIG), uz dodatni TIG gorionik

Integrirani dodavač žice, na kolicima sa točkovima

Jednostavno podešavanje parametara preko tri potenciometra na kontrolnom panelu - struja zavarivanja, napon luka, brzina dodavanja žice

Prihvati i malih i standardnih kalemova žice - do 15 kg

Brza i jednostavna zamena polariteta kod rada sa punjenim žicama predviđenim za MINUS pol

U saglasnosti sa Evropskim specifikacijama: 2011/65 / EU, 2014/35 / EU, 2014/30 / EU i IEC 60974.

Isporuka obuhvata osnovni uređaj na platformi sa točkovima, napojni kabl, kabl za masu sa piključkom, kabl za REL zavarivanje sa držačem elektrode i pištolj Binzel 15AK, 3m

Garancija: 2 godine - Servis i rezervni delovi su obezbedjeni – **Galeb Group / Galeb System**

TEHNIČKE KARAKTERISTIKE

Maksimalna struja zavarivanja	200 A
Prečnik žice za zavarivanje	0,8-1,0mm
Prečnik obložene elektrode - REL postupak	1,6 - 5,0mm
Intermitenca na 40°C	
Pri 60% opterećenja	200 A
Angažovana snaga pri napajanju preko agregata	6 kVA
Napon	230V 1-ph
Dimenzije (D x Š x V)	230 x 500 x 360 mm
Masa	22,0 kg

Info: www.galeb.com

E-mail: info@galeb.com

Tel: 015/367-700